

## Technische Daten Abkantmaschinen / Scheren

Farina	CFO 205	CFO 208	CFO 210	CFO 212	CFO 214	CFO 216	CFO 220	CFO 225	CFO 230	CFO 305	CFO 306	CFO 308	CFO 310
Schneidlänge (mm)	2100	2100	2100	2100	2100	2100	2100	2100	2100	3100	3100	3100	3100
Distanz zwischen Ständer (mm)	2200	2200	2200	2200	2200	2200	2300	2300	2300	3200	3200	3200	3200
Aussparung (mm)	500	500	500	500	500	500	500	500	500	500	500	500	500
Schneidkraft (KN)	200	360	480	510	710	860	1400	1800	2400	200	260	360	480
max. Blechdicke (mm)	5	8	10	12	14	16	20	25	30	5	6	8	10
Schneidwinkel (Grad)	30'–3°	30'–3°	30'–3°	30'–3°	30'–3°	30'–3°	30'–3°	30'–3°	30'–3°	30'–3°	30'–3°	30'–3°	30'–3°
Hübe pro min. (min/max)	35/60	31/52	25/48	22/40	20/38	19/37	15/25	13/23	9/18	35/60	33/58	31/52	25/48
Hinteranschlag Hub (mm)	750	750	750	750	1020	1020	1020	1020	1020	750	750	750	750
Motor Leistung (kW)	7.5	11	18.5	22	22	30	37	45	55	7.5	11	15	18.5
Gewicht (kg)	4900	6900	7900	8800	10000	12600	15500	18000	21800	7000	8700	9600	11800
Länge (mm)	2750	2750	2750	2850	2850	2850	2900	2900	2900	3600	3600	3600	3800
Breite (mm)	2000	2000	2200	2200	2200	2200	2300	2400	2500	1800	1800	2000	2200
Höhe (mm)	1900	1900	1900	2300	2300	2400	2500	2500	2800	1900	1900	1900	2200

## Technische Daten Abkantmaschinen / Scheren

Farina	CFO 313	CFO 316	CFO 320	CFO 325	CFO 330	CFO 405	CFO 406	CFO 408	CFO 410	CFO 412	CFO 415	CFO 418	CFO 423
Schneidlänge (mm)	3100	3100	3100	3100	3100	4100	4100	4100	4100	4100	4100	4100	4100
Distanz zwischen Ständer (mm)	3200	3200	3300	3300	3300	4200	4200	4200	4200	4200	4200	4300	4300
Aussparung (mm)	500	500	500	500	500	500	500	500	500	500	500	500	500
Schneidkraft (KN)	560	860	1250	1800	2400	290	300	380	460	850	1100	1300	1900
max. Blechdicke (mm)	13	16	20	25	30	5	6	8	10	12	15	18	23
Schneidwinkel (Grad)	30'–3°	30'–3°	30'–3°	30'–3°	30'–3°	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'
Hübe pro min. (min/max)	22/40	19/37	15/25	13/23	9/18	33/58	33/58	25/48	22/45	20/41	19/37	16/26	12/22
Hinteranschlag Hub (mm)	1020	1020	1020	1020	1020	750	750	750	750	750	1020	1020	1020
Motor Leistung (kW)	22	30	45	45	55	11	15	15	18.5	22	30	37	45
Gewicht (kg)	1400	17800	20800	26000	31500	12900	13600	16000	18800	21600	24000	28500	33000
Länge (mm)	3800	3800	3900	3900	3900	4650	4650	4650	4700	4700	4900	4900	5000
Breite (mm)	2200	2200	2400	2500	2600	2000	2000	2300	2400	2400	2400	2500	2700
Höhe (mm)	2400	2400	2600	3900	3000	1900	1900	1900	2200	2300	2400	2600	2850

## Technische Daten Abkantmaschinen / Scheren

Farina	CFO 428	CFO 605	CFO 606	CFO 608	CFO 610	CFO 612	CFO 615	CFO 618	CFO 623	CFO 625
Schneidlänge (mm)	4100	6100	6100	6100	6100	6100	6100	6100	6100	6100
Distanz zwischen Ständer (mm)	4300	6300	6300	6300	6300	6300	6300	6300	6300	6300
Aussparung (mm)	500	100	100	100	100	100	100	100	100	100
Schneidkraft (KN)	2300	290	300	380	460	850	1100	1300	900	2300
max. Blechdicke (mm)	28	5	6	8	10	12	15	18	23	25
Schneidwinkel (Grad)	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'	30'–2°30'
Hübe pro min. (min/max)	9/16	26/47	25/45	23/40	22/38	22/35	18/30	15/26	12/22	9/15
Hinteranschlag Hub (mm)	1020	750	750	750	750	1020	1020	1020	1020	1020
Motor Leistung (kW)	55	11	18.5	18.5	22	30	37	37	45	55
Gewicht (kg)	38000	20800	23500	28000	32000	35000	41500	47000	52000	62000
Länge (mm)	5000	6750	6750	6750	6850	6850	6850	6950	6950	6950
Breite (mm)	2800	2500	2500	2700	2800	2900	2900	3000	3100	3200
Höhe (mm)	3200	2200	2200	2400	2500	2600	2700	2800	3000	3100