

Technische Daten Abkantmaschinen / Scheren

Farina	40/16	40/20	65/25	65/30	80/30	80/40	110/30	110/40	130/30	130/40	160/30	160/40	160/60
Biegekraft (KN)	400	400	650	650	800	800	1100	1100	1300	1300	1600	1600	1600
Biegelänge (mm)	1670	2085	2505	3150	3250	4100	3150	4175	3150	4175	3150	4100	6100
Distanz zwischen Ständer (mm)	1450	1670	2100	2600	2300	3600	2600	3600	2300	3600	2600	3600	5600
Ausladung (mm)	300	300	300	300	500	500	500	500	500	500	500	500	500
Abstand Tisch Stößel (mm)	380	380	380	380	400	400	445	445	445	445	445	445	445
Zylinder Hub (mm)	200	200	200	200	200	200	250	250	250	250	250	250	250
Annäherungsgeschw. (mm/s)	125	125	125	125	125	125	120	120	110	110	100	100	100
Arbeitgeschw. (mm/s)	0–10	0–10	0–10	0–10	0–10	0–10	0–10	0–10	0–10	0–10	0–10	0–10	0–10
Rückfahrgeschw. (mm/s)	120	120	120	120	120	120	120	120	120	120	100	100	100
Motor Leistung (KN)	4	4	7.5	7.5	11	11	11	11	15	15	15	15	15
Gewicht (kg)	3050	3200	4200	4450	6950	8400	7800	10 700	10 400	13 100	12 800	15 400	20 000
Länge (mm)	2450	2900	3400	3980	3980	4980	3990	4980	3990	4980	3950	4950	5950
Breite (mm)	1260	1260	1500	1690	1750	1750	1750	1750	1750	1750	1930	1930	1930
Höhe (mm)	2200	2300	2350	2450	2740	2740	2800	3100	2900	3100	2800	3100	3450

Technische Daten Abkantmaschinen / Scheren

Farina	200/30	200/40	200/60	250/30	250/40	250/60	320/40	320/60	400/40	400/60	400/80	500/40	500/60
Biegekraft (KN)	2000	2000	2000	2500	2500	2500	3200	3200	4000	4000	4000	5000	5000
Biegelänge (mm)	3150	4100	6100	3150	4100	6100	4100	6100	4100	6100	8100	4100	6100
Distanz zwischen Ständer (mm)	2600	3600	5600	2600	3600	5600	3600	5600	3600	5600	7050	3600	5500
Ausladung (mm)	500	500	500	500	500	500	500	500	500	500	500	500	500
Abstand Tisch Stößel (mm)	525	525	525	630	630	630	630	630	630	630	630	630	630
Zylinder Hub (mm)	275	275	275	275	275	275	350	350	350	350	350	350	350
Annäherungsgeschw. (mm/s)	100	100	100	100	100	100	100	100	80	80	80	80	80
Arbeitgeschw. (mm/s)	0–10	0–10	0–10	0–10	0–10	0–10	0–8	0–8	0–8	0–8	0–8	0–7	0–7
Rückfahrgeschw. (mm/s)	100	100	100	100	100	100	100	100	80	80	80	70	70
Motor Leistung (KN)	18.5	18.5	18.5	18.5	18.5	18.5	22	22	30	30	30	37	37
Gewicht (kg)	14 900	18 500	25 500	15 200	25 000	31 000	28 000	40 400	32 000	4100	54 000	40 000	51 000
Länge (mm)	4000	4950	6950	4000	4950	6950	4950	6950	4950	6950	8950	4950	6950
Breite (mm)	2050	2050	2050	2150	2150	2250	2350	2480	2480	2480	2480	2490	2490
Höhe (mm)	3150	3500	37000	3100	3250	3480	3690	4050	3700	3850	4250	3700	3850

Technische Daten Abkantmaschinen / Scheren

Farina	500/80	650/40	650/60	650/80
Biegekraft (KN)	5000	6500	6500	6500
Biegelänge (mm)	8100	4100	6100	8100
Distanz zwischen Ständer (mm)	7050	3600	5100	7050
Ausladung (mm)	500	500	500	500
Abstand Tisch Stößel (mm)	630	630	630	630
Zylinder Hub (mm)	350	350	350	350
Annäherungsgeschw. (mm/s)	80	70	70	70
Arbeitgeschw. (mm/s)	0–7	0–7	0–7	0–7
Rückfahrgeschw. (mm/s)	70	65	65	65
Motor Leistung (KN)	37	45	45	45
Gewicht (kg)	65 000	48 000	60 000	77 000
Länge (mm)	8950	4950	6950	8950
Breite (mm)	2490	2490	2490	2490
Höhe (mm)	4250	3850	4150	4450