

Technische Daten Horizontalbiegepressen / Profilbiegemaschinen / Ausklinkmaschinen

AMOB	CH-35-CN2	CH-42-CN2	CH-60-CN2	CH-80-CN2	CH-100-CN2
max. Biegeleistung Rundmat. OD x Mat.-Stärke Stahl 450 N/mm ² (mm)	35 x 2 mm	42 x 2 mm	60 x 3 mm	80 x 3.5 mm	104 x 4
max. Biegeleistung Rundmat. OD x Mat.-Stärke Stahl 700 N/mm ² (mm)	28 x 2	38 x 1.5	50.8 x 2	76 x 1.5	100 x 1.5
max. Biegeleistung Vierkantmat. B x H x Mat.-Stärke Stahl 450 N/mm ² (mm)	25 x 25 x 2	35 x 35 x 2	50 x 50 x 3	60 x 60 x 4 mm	80 x 80 x 5
max. Widerstandsmoment Stahl 450 N/mm ² (cm ³)	1.6	2.7	8.3	15.7	30
max. Biegeradius (mm)	105	110	220	250	310
max. Materiallänge (mm)	2500	2500	3000	3500	4000
Motorleistung (kW)	4.1	4.1	15.1	15.4	30.3
Abmessung L x B x H (mm)	4100 x 1300 x 800	4500 x 1250 x 1150	5000 x 1250 x 1150	5600 x 1500 x 1350	6800 x 1750 x 1800
Gewicht (kg)	2700	3400	4000	4200	7200